

2104

Test Sieve Shaker

Information

Test Sieve Shaker EML 200 Premium for dry sieving

The Test Sieve Shaker EML 200 Premium offers a comfort improvement – the machine is much quieter than ever before. Transmission of vibrations to the base is greatly reduced utilising an improved dampening system.

The new Test Sieve Shaker Premium is ideally suited for users who demand precision and reproducible sieve analyses.

- three-dimension sieving action
- extra quiet electromagnetic drive
- free selectable amplitude up to 3 mm
- improved damping system
- extra-large display of remaining sieving time
- Ethernet interface
- network-voltage- and frequency independent
- CSA 5.0 Basic license included when purchasing a Test Sieve Shaker

Technical Specifications

Technical Data:

- Applications: dry sieving
- Sieve diameters: Ø 50, 76.2 (3”), 100, 150, 200, 203 (8”)
- Sample weight: approx. 3 kg
- Weight of sieve set: max. 8.7 kg
- Operating voltage: 110 – 220 Volt, 50 – 60 Hertz
- Amplitude: free selectable amplitude up to 3 mm
- Timer: 0-99 minutes or permanent operating
- Sound emission: ≤ 70 dBA
- Program memory locations: 01 – 49
- Clamping system: classic

- Weight: approx. 37 kg, net
- Dimensions: 385 × 295 × 800 mm

Item-No.: 21040